



## Features

- Replaces traditional 6" CFL, HID or Incandescent commercial down lights
- Efficient thermal design, with long lifespan of 25,000hrs
- 0-10V dimmable driver
- Optional color temperatures available
- UL and Energy Star certified



5 YEAR WARRANTY

## Recommended Applications

- Ideal for retrofit applications such as hotel lobby, retail shopping, supermarkets, recreation centers, public areas, garage, corridors, offices, reception areas, schools, hospitality etc.



Ordering	Input	Luminaire	Wattage	CCT	Initial	Luminaire	Rated	CRI	Power	Dimmable	Certificate
Code	Voltage(VAC)	Shape	(W)		Lumens(lm)	Efficacy(lpw)	Life(hrs)		Factor		
CDW25DR627KAH	100-277	6"Downlight	25	2700K	2200	88	35000	80	0.9	0-10V Dimmable	UL/Energy Star
CDW25DR630KAH	100-277	6"Downlight	25	3000K	2250	90	35000	80	0.9	0-10V Dimmable	UL/Energy Star
CDW25DR635KAH	100-277	6"Downlight	25	3500K	2300	92	35000	80	0.9	0-10V Dimmable	UL/Energy Star
CDW25DR640KAH	100-277	6"Downlight	25	4000K	2400	96	35000	80	0.9	0-10V Dimmable	UL/Energy Star
CDW25DR650KAH	100-277	6"Downlight	25	5000K	2450	98	35000	80	0.9	0-10V Dimmable	UL/Energy Star
CDW35DR627KAH	100-277	6"Downlight	35	2700K	3000	86	35000	80	0.9	0-10V Dimmable	UL
CDW35DR630KAH	100-277	6"Downlight	35	3000K	3050	87	35000	80	0.9	0-10V Dimmable	UL
CDW35DR635KAH	100-277	6"Downlight	35	3500K	3100	89	35000	80	0.9	0-10V Dimmable	UL
CDW35DR640KAH	100-277	6"Downlight	35	4000K	3200	91	35000	80	0.9	0-10V Dimmable	UL
CDW35DR650KAH	100-277	6"Downlight	35	5000K	3300	94	35000	80	0.9	0-10V Dimmable	UL

1. CCT range complies to ANSI C78.377-2011
2. Rated average life based on engineering testing and probability analysis
3. Lifetime test consistent with IESNA LM80 lumen maintenance procedure

**Product Dimension(mm)**

